

## 轴承压入型 · 轴承拆卸型


### 订购编号示例

<b>1</b> 代号	-	<b>2</b> D	-	<b>3</b> dr 规格	-	<b>4</b> L	-	<b>5</b> H	-	<b>6</b> X	-	<b>7</b> Y	-	<b>8</b> Z	-	<b>9</b> 材料代码
BFSBC	-	40	-	15	-	60	-	H0.8	-		-		-		-	H
BFSBR	-	60	-	20	-	70	-		-	X12	-	Y4.6	-	Z10	-	H
BFSCD	-	25	-		-	28	-		-		-		-		-	F


### 轴承压入式




轴承压入型



直柱型  
BFSBD



圆弧型  
BFSBC



肋槽型  
BFSBR

其余<sup>1/3</sup>

注：轴承不可拆卸, 轴承采用压入式。

代号	类型	1 材料代码	材质	表面处理	轴承材质
BFSBD BFSBC BFSBR	轴承压入式	H	铝合金	本色阳极氧化	钢



1 代号	主要尺寸		主要尺寸				配套轴承								
	2 D	3 dr	4 L 指定单位 10mm	5 H (圆弧型时选择)	6 X 肋槽型肋槽尺寸指定单位 0.1mm	7 Y	8 Z	D <sub>2</sub>	公称型号						
BFSBD BFSBC BFSBR	15	5	直柱型·圆弧型 25-100 肋槽型 50-100 L > B×2+2	0.3 0.5 0.8	-	-	-	7	RM67/5-2Z	8	2.5				
		9						RM67/6-2Z	10	3					
		10						RM68/6-2Z	13	5					
	20	6						10	4.0 ~ 6.0	7.0 ~ 15.0	5.0 ~ 12.0	10	RM67/8-2Z	12	3.5
		8										RM69/6-2Z	15	5	
		10										RM68/8-2Z	16	5	
	25	6						15	4.0 ~ 7.0	7.0 ~ 15.0	5.0 ~ 12.0	10	RM69/8-2Z	19	5
		8										R6900-2Z	22	6	
		12										R6901-2Z	24	6	
	30	8						20	4.0 ~ 6.0	7.0 ~ 15.0	5.0 ~ 12.0	15	R6902-2Z	28	7
		10										RM629-2Z	24	7	
		12										R6000-2Z	26	8	
	35	10						25	4.0 ~ 6.0	7.0 ~ 15.0	5.0 ~ 12.0	17	R6901-2Z	24	6
		12										R6902-2Z	28	7	
		15										RM629-2Z	24	7	
	40	12						30	4.0 ~ 6.0	7.0 ~ 15.0	5.0 ~ 12.0	17	R6000-2Z	26	8
		15										R6901-2Z	24	6	
		20										R6902-2Z	28	7	
	50	10						35	4.0 ~ 6.0	7.0 ~ 15.0	5.0 ~ 12.0	22	R6804-2Z	32	7
		12										R6200-2Z	30	9	
		15										R6001-2Z	28	8	
	60	12						40	4.0 ~ 6.0	7.0 ~ 15.0	5.0 ~ 12.0	17	R6902-2Z	28	7
		15										R6904-2Z	37	9	
		20										R6905-2Z	42	10	
80	12	45	4.0 ~ 6.0	7.0 ~ 15.0	5.0 ~ 12.0	27	R6201-2Z	32	10						
	15					R6002-2Z	27	9							
	25					R6904-2Z	37	9							
	30	50	4.0 ~ 6.0	7.0 ~ 15.0	5.0 ~ 12.0	32	R6905-2Z	42	9						
	35					R6906-2Z	47	15							
	35					R6205-2Z	52	15							
	35	50	4.0 ~ 6.0	7.0 ~ 15.0	5.0 ~ 12.0	41	R6006-2Z	52	13						
	35					R6907-2Z	55	10							

▲ BFSBR 仅适用于 D ≥ 30 以上的规格。

### 轴承拆卸式



轴承拆卸型



轴承拆卸型  
BFSCD

其余<sup>1/3</sup>

注：轴承可拆卸

代号	类型	1 材料代码	材质	表面处理	轴承材质
BFSCD	轴承拆卸式	F	45#	四氧化三铁保护膜	钢
		G	45#	无电解镀锌	
		H	铝合金	本色阳极氧化	

1 代号	主要尺寸		主要尺寸				配套轴承												
	2 D	3 dr	4 L	5 H	6 X	7 Y	8 Z	D <sub>2</sub>	公称型号										
BFSCD	20	38	45	50	-	-	-	6	15	RS69/6-2Z	15	5	1.2	17					
		25	38	45						50	60	RS606-2Z			17	6			
		30	38	45						50	60	70			RM69/8-2Z	19	-		
	30A	38	45	50				60	70	8	22	22	RS608-2Z	22	7	1.5	25		
		35	38	45				50	60				70	85	90	R6000-2Z	26	8	-
		40	38	45				50	60				70	85	90				
	40A	38	45	50				60	70	85	90	10							

皮带惰轮