


08A 系列传动链轮

■ 产品特点: 产品内孔标准化, 可直接用于现场安装。




对应链条尺寸系列

08A



▲ 键槽中心对准齿尖中心

08A系列



代号	材质	热处理	表面处理	附件
DSFA08AB	45#	齿部高频淬火 HRC35-45	无	紧定螺钉
DSFB08AB			发黑	
DSFC08AB	304	无	无	

订购编号示例

1 代号 - 2 齿数 - 3 dr

DSFB08AB - 14 - 14

1 代号	2 齿数	主要尺寸					重量			
		3 孔径 dr	节径 D	外径 D1	凸台直径 D2	总长 L	a	kg		
DSFA08AB DSFB08AB	▲ 9	10 12 14 15	37.13	42	28	22	5	0.11		
	▲ 10	10 12 14 15 16 17 18	41.1	46	32			0.14		
	▲ 11	10 12 14 15 16 17 18 19 20	45.08	51	36			0.19		
	▲ 12	10 12 14 15 16 17 18 19 20 22	49.07	55	40			0.22		
	13	12 14 15 16 17 18 19 20 22 24 25	53.07	59	37			0.23		
	14	12 14 15 16 17 18 19 20 22 24 25 28	57.07	63	42			0.28		
	15	12 14 15 16 17 18 19 20 22 24 25 28 30	61.08	67	46		6	0.34		
	16	14 15 16 17 18 19 20 22 24 25 28 30 32	65.1	71	50			0.4		
	17	14 15 16 17 18 19 20 22 24 25 28 30 32 35	69.12	76	54			0.46		
	18	14 15 16 17 18 19 20 22 24 25 28 30 32 35 40	73.14	80	57			0.51		
	19	14 15 16 17 18 19 20 22 24 25 28 30 32 35 38 40	77.16	84	62			0.59		
	20		81.18	88	67			0.76		
	21	14 15 16 17 18 19 20 22 24 25 28 30 32 35 38 40 42 45	85.21	92	71	25	7	0.85		
	22		89.24	96	75			0.95		
	23		93.27	100	77			1		
	24		97.3	104				0.84		
	25	14 15 16 17 18 19 20 22 24 25 28 30 32 35 38 40 42	101.33	108	63			0.88		
	26		105.36	112				0.92		
	28		113.43	120				1		
	30		121.5	128						
	32	20 22 24 25 28 30 32 35 40	129.57	137	68	28	10	1.3		
	34		137.64	145				1.3		
	35		141.68	149				1.4		
	36		145.72	153				1.5		
	38	24 25 28 30 32 35 40	153.79	161				1.6		
	40	25 28 30 32 35 40	161.87	169				1.7		
	DSFC08AB	▲ 10	12 15 16	41.1	46	32	22	5	0.14	
		▲ 11		45.08	51	36			0.19	
		▲ 12	15 16 18 20	49.07	55	40			0.22	
		13		53.07	59	37			0.23	
		14	15 16 18 19 20 22 24 25	57.07	63	42			0.28	
		15	15 16 18 19 20 22 24 25 28	61.08	67	46			0.34	
16			65.1	71	50	6		0.4		
17			69.12	76	54			0.46		
18		15 16 18 19 20 22 24 25 28 30	73.14	80	57			0.51		
19			77.16	84	62			0.59		
20			81.18	88	67			0.76		
21			85.21	92	71	25	7	0.85		
22			89.24	96	75			0.95		
23		18 20 22 24 25 28 30	93.27	100	77			1		
24			97.3	104				0.84		
25			101.33	108	63			0.88		
26			105.36	112				0.92		
28			113.43	120				1		
30			121.5	128						
32		20 22 25 30	129.57	137	68	28	10	1.3		
35			141.68	149				1.4		
36			145.72	153				1.5		
40			161.87	169				1.7		

■ 轴孔加工尺寸

轴孔直径 dr	键槽 b × l ₂	固定螺丝 M
10	3 × 1.4	M4
12	4 × 1.8	M5
14 ~ 17	5 × 2.3	M6
18 ~ 22	6 × 2.8	M6
24 ~ 30	8 × 3.3	M8
32 ~ 38	10 × 3.3	M8
39 ~ 44	12 × 3.3	M8
45	14 × 3.8	M10

■ 带有▲的产品在轮毂外径上带有槽口, 尺寸如下表

齿数	s	GD
9	5.2	23
10		27
11		31
12		35