



外径基准型（最大压缩量 27%~40%）



SCHDBA
SCHDBB
外径基准型

外径D 10mm以下 $\begin{smallmatrix} 0 \\ -0.5\text{mm} \end{smallmatrix}$
12mm以上 $\begin{smallmatrix} 0 \\ -0.8\text{mm} \end{smallmatrix}$

订购编号示例

1 代号 - 2 D - 3 L
SCHDBA - 5 - 35

劲度系数

▲ D12 仅限 SCHDAB、SCHDAC、SCHDAD、SCHDD 型。D14 仅限 SCHDD 型。

D	SCHDAA	SCHDAB	SCHDAC	SCHDAD	SCHDBA	SCHDBB	SCHDCA	SCHDCB	SCHDD								
2	—	0.05 (0.005)	0.2 (0.02)	0.3 (0.03)	0.5 (0.05)	—	—	—	—								
3	0.05N/mm (0.005kgf/mm)	0.098N/mm (0.01kgf/mm)	0.29N/mm (0.03kgf/mm)	0.49N/mm (0.05kgf/mm)	0.98N/mm (0.1kgf/mm)	1.5 (0.15)		2 (0.2)	2.9 (0.3)	4.9 (0.5)							
4						2.0N/mm (0.2kgf/mm)											
5							2.9N/mm (0.3kgf/mm)	5.9N/mm (0.6kgf/mm)	9.8N/mm (1.0kgf/mm)								
6		—								0.2N/mm (0.02kgf/mm)	0.5 (0.05)	0.98 (0.1)	2.9 (0.3)	3.9 (0.4)	4.9 (0.5)	9.8N/mm (1.0kgf/mm)	19.6N/mm (2.0kgf/mm)
8																	
10																	
12																	
13	14.7 (1.5)	29.4 (3.0)															
14																	
16																	
20	S = L×71%	0.3 (0.03)	0.5 (0.05)	0.98 (0.1)	2.9 (0.3)	3.9 (0.4)	4.9 (0.5)	14.7 (1.5)	29.4 (3.0)								
S		S = L×75%	S = L×60%	S = L×45%	S = L×40%	S = L×40%	S = L×35%	S = L×30%	S = L×25%								

▲ 蓝色型号和参数均为外径基准型（最大压缩量 27%~40%）型号

代号	类型	材质	弹簧常数
SCHDBA SCHDBB	外径基准型	SUS304-SWPB	± 10%

SCHDBA: S (工作行程) = L×40%

1 代号	2 D	3 L	d	压紧长度	S	载荷	
						(N)	(kgf)
SCHDBA	2	5 ▲	0.2	1.65	2	0.98	0.1
		10 ▲	0.26	5.07	4	1.96	0.2
		15 ▲	0.26	5.07	6	2.94	0.3
		20 ▲	0.3	9.9	8	3.92	0.4
		25 ▲	0.32	14.1	10	4.9	0.5
		30 ▲	0.32	14.1	12	5.88	0.6
	3	5 ▲	0.3	2	2	0.2	0.2
		10 ▲	0.35	3.7	4	3.9	0.4
		15 ▲	0.4	6.6	6	5.9	0.6
		20 ▲	0.4	6.6	8	7.8	0.8
		25 ▲	0.45	11.7	10	9.8	1
		30 ▲	0.45	11.7	12	11.8	1.2
	4	35 ▲	0.45	11.7	14	13.7	1.4
		40 ▲	0.5	20	16	15.7	1.6
		5 ▲	0.35	2.1	2	2	0.2
		10 ▲	0.45	5.3	4	3.9	0.4
		15 ▲	0.45	5.3	6	5.9	0.6
		20 ▲	0.5	8	8	7.8	0.8
	6	25 ▲	0.5	8	10	9.8	1
		30 ▲	0.55	12.7	12	11.8	1.2
		35 ▲	0.55	12.7	14	13.7	1.4
		40	0.6	19.8	16	15.7	1.6
		45	0.6	19.8	18	17.7	1.8
		50	0.6	19.8	20	19.6	2

1 代号	2 D	3 L	d	压紧长度	S	载荷	
						(N)	(kgf)
SCHDBA	5	5 ▲	0.4	2.2	2	2	0.2
		10 ▲	0.5	4.75	4	3.9	0.4
		15 ▲	0.5	4.75	6	5.9	0.6
		20 ▲	0.55	6.88	8	7.8	0.8
		25 ▲	0.55	6.88	10	9.8	1
		30	0.65	14.95	12	11.8	1.2
	6	35	0.65	14.95	14	13.7	1.4
		40	0.65	14.95	16	15.7	1.6
		45	0.7	21.7	18	17.7	1.8
		50	0.7	21.7	20	19.6	2
		60	0.75	30.75	24	23.5	2.4
		5 ▲	0.45	2.3	2	2	0.2
	7	10 ▲	0.55	4.4	4	3.9	0.4
		15 ▲	0.55	4.4	6	5.9	0.6
		20	0.65	8.5	8	7.8	0.8
		25	0.65	8.5	10	9.8	1
		30	0.7	12.6	12	11.8	1.2
		35	0.7	12.6	14	13.7	1.4
	8	40	0.7	12.6	16	15.7	1.6
		45	0.75	17.3	18	17.7	1.8
		50	0.75	17.3	20	19.6	2
		60	0.8	24.8	24	23.5	2.4
		70	0.8	24.8	28	27.5	2.8

外径基准型（最大压缩量 27%~40%）

■ SCHDBA: S(工作行程) = L×40%

1 代号	2 D	3 L	d	压紧长度	S	载荷	
						(N)	(kgf)
SCHDBA	8	10	0.65	4.6	4	3.9	0.4
		15	0.75	8.3	6	5.9	0.6
		20	0.75	8.3	8	7.8	0.8
		25	0.75	8.3	10	9.8	1
		30	0.8	10.4	12	11.8	1.2
		35	0.8	10.4	14	13.7	1.4
		40	0.8	10.4	16	15.7	1.6
		45	0.85	14.5	18	17.7	1.8
		50	0.85	14.5	20	19.6	2
		60	0.9	18	24	23.5	2.4
	10	70	1	30	28	27.5	2.8
		80	1	30	32	31.4	3.2
		10	0.75	4.7	4	3.9	0.4
		15	0.8	6.2	6	5.9	0.6
		20	0.8	6.2	8	7.8	0.8
		25	0.9	9.5	10	9.8	1
		30	0.9	9.5	12	11.8	1.2
		35	0.9	9.5	14	13.7	1.4
		40	1	15.5	16	15.7	1.6
		45	1	15.5	18	17.7	1.8
	12	50	1	15.5	20	19.6	2
		60	1.1	23.7	24	23.5	2.4
		70	1.1	23.7	28	27.5	2.8
		80	1.1	23.7	32	31.4	3.2
		15	0.9	6.75	6	5.9	0.6
		20	1	10	8	7.8	0.8
		25	1	10	10	9.8	1
		30	1.1	14.85	12	11.8	1.2
		35	1.1	14.85	14	13.7	1.4
		40	1.2	21.6	16	15.7	1.6
	13	45	1.2	21.6	18	17.7	1.8
		50	1.2	21.6	20	19.6	2
		60	1.3	32.5	24	23.5	2.4
		70	1.3	32.5	28	27.5	2.8
		80	1.4	46.2	32	31.4	3.2
		15	0.9	5.4	6	5.9	0.6
		20	1	8.25	8	7.8	0.8
		25	1	8.25	10	9.8	1
		30	1.1	12.1	12	11.8	1.2
		35	1.1	12.1	14	13.7	1.4
	16	40	1.1	12.1	16	15.7	1.6
		45	1.2	16.8	18	17.7	1.8
		50	1.2	16.8	20	19.6	2
		60	1.2	16.8	24	23.5	2.4
		70	1.4	35	28	27.5	2.8
		80	1.4	35	32	31.4	3.2
		15	1.1	7.7	6	5.9	0.6
		20	1.1	7.7	8	7.8	0.8
		25	1.2	10.8	10	9.8	1
		30	1.2	10.8	12	11.8	1.2
	20	35	1.3	14.3	14	13.7	1.4
		40	1.3	14.3	16	15.7	1.6
		45	1.4	19.6	18	17.7	1.8
		50	1.4	19.6	20	19.6	2
		60	1.4	19.6	24	23.5	2.4
		70	1.5	27	28	27.5	2.8
		80	1.5	27	32	31.4	3.2
		20	1.6	10.4	8	23.5	2.4
		25	1.6	10.4	10	29.4	3
		30	1.7	12.8	12	35.3	3.6
		35	1.7	12.8	14	41.2	4.2
	20	40	1.8	15.3	16	47.1	4.8
		45	1.8	15.3	18	53	5.4
		50	2	23	20	58.8	6
		60	2	23	24	70.6	7.2
		70	2.2	35.2	28	82.4	8.4
		80	2.2	35.2	32	94.1	9.6

▲ kgf(载荷) = N/mm(刚度系数) × 0.101972 × S(工作行程) kgf = N × 0.101972
 ▲ 所有带▲号的 SCHDBA 型两端面均未进行磨削加工
 ▲ 压紧长度为参考值。因批次不同会有少许差异
 ▲ 理论使用次数: 100 万次 (非保证值)

■ SCHDBB: S(工作行程) = L×Fa%

1 代号	2 D	3 L	d	压紧长度	S	载荷		Fa%
						(N)	(kgf)	
SCHDBB	3	5 ▲	0.35	2.8	2	2.9	0.3	40
		10 ▲	0.4	4.8	4	5.9	0.6	
		15 ▲	0.45	8.3	6	8.8	0.9	
		20 ▲	0.45	8.3	6	8.8	0.9	30
		25 ▲	0.5	14	8	11.8	1.2	32
		30 ▲	0.5	14	8	11.8	1.2	27
	4	5 ▲	0.4	2.6	2	2.9	0.3	
		10 ▲	0.45	3.9	4	5.9	0.6	
		15 ▲	0.5	6	6	8.8	0.9	40
		20 ▲	0.55	9.4	8	11.8	1.2	
		25	0.6	14.4	10	14.7	1.5	
		30	0.6	14.4	10	14.7	1.5	33
		5 ▲	0.45	2.6	2	2.9	0.3	
		10 ▲	0.5	3.6	4	5.9	0.6	
		15	0.6	7.5	6	8.8	0.9	40
		20	0.6	7.5	8	11.8	1.2	
	5	25	0.65	10.7	10	14.7	1.5	
		30	0.7	15.4	12	17.7	1.8	
		35	0.7	15.4	14	20.6	2.1	
		5 ▲	0.5	2.4	2	3.9	0.4	
		10	0.6	4.2	4	7.8	0.8	
		15	0.7	7.4	6	11.8	1.2	40
		20	0.7	7.4	8	15.7	1.6	
		25	0.8	13.6	10	19.6	2	
		30	0.8	13.6	12	23.5	2.4	
		35	0.85	17.5	14	27.5	2.8	
	6	40	0.9	23.4	16	31.4	3.2	
		45	0.9	23.4	18	35.3	3.6	
		50	0.9	23.4	18	35.3	3.6	36
		60	1	41	18	35.3	3.6	30
		70	1	41	24	47.1	4.8	34
	8	10	0.75	5.3	4	7.8	0.8	
		15	0.75	5.3	6	11.8	1.2	
		20	0.9	10.4	8	15.7	1.6	
		25	0.9	10.4	10	19.6	2	
		30	1	17	12	23.5	2.4	40
		35	1	17	14	27.5	2.8	
		40	1	17	16	31.4	3.2	
		45	1.1	25.3	18	35.3	3.6	
		50	1.1	25.3	20	39.2	4	
		60	1.1	25.3	24	47.1	4.8	
	10	70	1.2	39.6	28	54.9	5.6	
		10	0.85	5.1	4	7.8	0.8	
		15	0.85	5.1	6	11.8	1.2	
		20	1	9.5	8	15.7	1.6	40
		25	1	9.5	10	19.6	2	
		30	1.1	14.3	12	23.5	2.4	
		35	1.1	14.3	14	27.5	2.8	
		40	1.2	20.4	16	31.4	3.2	
		45	1.2	20.4	18	35.3	3.6	
		50	1.2	20.4	20	39.2	4	
	13	60	1.3	29.9	24	47.1	4.8	
		70	1.4	43.4	24	47.1	4.8	34
		15	1	5.75	6	11.8	1.2	
		20	1.2	10.5	8	15.7	1.6	
		25	1.2	10.5	10	19.6	2	
		30	1.3	15	12	23.5	2.4	
		35	1.3	15	14	27.5	2.8	
		40	1.4	20.3	16	31.4	3.2	40
		45	1.4	20.3	18	35.3	3.6	
		50	1.5	27.8	20	39.2	4	
	16	60	1.5	27.8	24	47.1	4.8	
		70	1.6	38.4	28	54.9	5.6	
		80	1.6	38.4	32	62.8	6.4	
		15	1.2	7.2	6	11.8	1.2	
		20	1.3	9.1	8	15.7	1.6	
		25	1.3	9.1	10	19.6	2	
		30	1.4	12.3	12	23.5	2.4	
		35	1.5	16.5	14	27.5	2.8	
		40	1.6	21.6	16	31.4	3.2	40
		45	1.6	21.6	18	35.3	3.6	
	20	50	1.7	28	20	39.2	4	
		60	1.7	28	24	47.1	4.8	
		70	1.8	36	28	54.9	5.6	
		80	1.8	36	32	62.8	6.4	
		20	1.7	10.6	8	31.4	3.2	
		25	1.8	12.6	10	39.2	4	
		30	1.8	12.6	12	47.1	4.8	
		35	2	19	14	54.9	5.6	
		40	2	19	16	62.8	6.4	40
		45	2	19	18	70.6	7.2	
		50	2.2	27.5	20	78.5	8	
	20	60	2.2	27.5	24	94.1	9.6	
		70	2.3	34.5	28	109.8	11.2	
		80	2.4	40.8	32	125.5	12.8	

▲ kgf(载荷) = N/mm(刚度系数) × 0.101972 × S(工作行程) kgf = N × 0.101972
 ▲ 所有带▲号的 SCHDBB 型两端面均未进行磨削加工
 ▲ 压紧长度为参考值。因批次不同会有少许差异
 ▲ 理论使用次数: 100 万次 (非保证值)